



The way this machine rotates around the goods is more suitable for wrapping lighter, taller and unstable products or overweight goods after palletizing. The rocker arm wrapping machine has flexible installation methods. It can be placed on the wall or fixed with a bracket. It can be connected to the conveyor line as needed to meet the needs of assembly line operations. It is widely used in food, beverage, chemical, papermaking, building materials and other industries.

Equipment features:

1. It truly realizes online unmanned operation, automatic identification, automatic start, automatic film loading and film cutting, and automatically transports to the waiting position after packaging, waiting for forklift unloading.
2. The equipment is welded with a steel structure. The whole machine is mainly divided into four modules: frame, arm, film loading and cutting mechanism and connected control system. The structure is simple, and the stability and durability are more outstanding

Technical parameters:

Product name	Online rocker arm Wrapping machine
Model	SPR-1800FZ
Supply voltage	3P 380V
Overall power	3.2kw
Winding specification	(800-1100)mm*(800-1200)mm
Packing height	800-2000mm
Packaging efficiency	20-40 pallets/h
Cantilever velocity	6-18rpm frequency adjustable
Cantilever system	Automatic cantilever reset, highly sensitive emergency brake system
Turntable bearing	2000kg
Wrap film	LLDPE stretch film W≤500mm;
Air consumption	1000ml/min
Machine weight	2500kg
Overall size	4300*2320*3530

Our equipment includes standard machines, customized machines, and models with optional functions.