



This machine is suitable for winding long strips, round tubes and other objects; the rotation of the swivel can realize the horizontal winding of the object; it has the function of variable frequency speed regulation, which can adjust various speeds at any time according to the actual object, so as to control the tension of the film and the overlapping width of the film; the function of variable frequency soft start and soft positioning makes the whole winding process smooth, and the accurate positioning can prevent the damage of the goods during the handling process, and play the role of dust, moisture and cleaning.

## Equipment features:

1. The operator manually adjusts the vertical rod to ensure the safety and stability of the goods.
2. The operation is simple, and the number of winding circles and film tension can be directly adjusted on the operation panel

## Technical parameters:

Product name	Vertical Ring Wrapping Machine
Model	SPR-FG-CTV-200BD
Power source	3P AC 380V 50/60 Hz
Air source	0.4MPa ~ 0.6MPa
Work Power	5.0 kW
Rotational speed	50 rpm
Transmission mode	Friction wheel drive
Tension adjustment	Friction mode
Film breaking mode	Electro thermal film breaking
Mucous mode	Electro thermal film
Pallet size	Max pallet 1100*1300mm(height1000~2000mm) Min Pallet: 500*600mm(height500~2000mm)
Packingmaterial	inner diam.Φ76mm, 可选内芯Φ50 mm, 最大外径Φ280mm

Our equipment includes standard machines, customized machines, and models with optional functions.